

Forced Ventilation Unit

Forced Ventilation Units type AH for three phase and single-phase connection



External cooling for electric motors driven by frequency inverter in IP 66, insul. Class F with UL/CSA approval



Forced Ventilation Units in IEC frame size 56 up to 200 - NEMA frame 48 to 286 with detachable extension (adapter)

- The extensions are available for all motor types - the diameter, the length and side punching, special dimensions can be made according to customer's requirements
- The special unidirectional optimized ventilation fans provide high air flow and low noise
- Application inputs: *Wide voltage range!*
 - 3-phase** 209-304 V D/361-525 V Y 50 Hz - 209-348 V D/361-603 V Y 60 Hz
 - 1-phase** 218-290 V D 50 Hz / 218-290 V D 60 Hz – **frame size > 160:** 209-283 V 50 Hz
- Applications up to **158° F max. for the complete multivolt range**
- Special shaft sealing system assures a long, safe service life
- Optional supply with thermal protection

Kurt Maier Motor-Press GmbH

Birkenweg 18 * DE - 37589 Kalefeld

☎ +49(0)5553 99 01 0 * 📠 +49(0)5553 99 01 88 * ✉ E-mail: info@kmmp.de * <http://www.kmmp.de>

MAC

In the USA: Motors Accessories & Components

☎ (804) 358-0260 📠 (804) 358-3589 ✉ sales@mac-usa.biz 🌐 www.mac-usa.biz

